Computer Science

CHAPTER 4
CONDITIONAL CONTROL STRUCTURE

Computer Science

SHORT AND LONG QUESTIONS

Q1. Define a control statement.

Ans. Control Statement

A control statement is a statement that is used to determine the sequence in which program instructions are executed. It controls the flow of execution of program and performs different actions.

Q2. Define a conditional statement.

Ans. Conditional Statement

A conditional statement is a statement in a programming language that controls conditions. When a conditional statement is executed, the first condition is checked and if it is true, then the statements in the body of the statement are executed. If a statement is executed and the condition is false, **it is then skipped** or executes statements.

Q3. What is the purpose and structure of a Statement? Explain with the help of examples.

Ans. Structure of Statement

The structure is as in the following general form: Syntax

if (condition)

{

Statement(s);

}

Block of statements

{

}

Computer Science

When the statement is executed, the condition is executed. If the condition is true then the block of statements within the braces will be executed. If the condition is false then the statements within the braces will be skipped. After the execution of the statement is completed or if the condition is false, the next statement after the statement is executed.

If there is only one statement to be executed then the condition is true then braces are optional.

Ans. Use of Statement (Example)

Program 1: The program to find the absolute value of a number.

```
#include<iostream.h>
#include<conio.h>
void main()
{
int num;
cout<<"Enter a number: ";
cin>>num;
if (num<0)
num=-num;
cout<<"Absolute value is: "<<num;
getch();
}
```

Program to demonstrate the use of statement

When the statement is executed, the condition is executed. If the condition is true then the block of statements within the braces will be executed. If the condition is false then the statements within the braces will be skipped. After the execution of the statement is completed or if the condition is false, the next statement after the statement is executed. The following two statements will be skipped and the program will terminate and there will be no output.

The output of the program is shown in Fig. If the inputted value was less than zero, it

Computer Science

Program 2: The program to flag out the invalid age (example).

```
#include<iostream.h>
#include<conio.h>
void main()
{
int age;
cout<<"Enter your age: ";
cin>>age;
if (age<0 || age>100)
cout<<"Invalid age";
getch();
}
```

Program to demonstrate use of statement

When the above program's executed, it will prompt the user to enter a number. If the number is less than zero or greater than 100, it will print the output of the number is Invalid flag.

Computer Science

Q4. What is the purpose and structure of a two statement? Explain with the help of examples.

Ans. Structure of the Statement

The **if else** statement is a two statement in which one or some of the two statements is executed. The **if else** statement is also called **two-way selection statement.**

The **if else** statement has the following general form **Syntax.**

if (condition)

{

Block of statements

}

else

{

Block of statements

}

Computer Science

When it does statement is executed, the condition is executed.

If the condition is true then the block of statements following it will be executed and the block of statements following will be skipped.

Computer Science

If the condition is false then the block of statements following it will be skipped and the block of statements following else will be executed.

After the execution of the statement is completed, the next statement after the statement is executed.

Ans. Use of Statement (Example)

Program 1: The program to find the average and pass fail the average student (example).

```
#include<iostream.h>
#include<conio.h>
void main()
{
int num1,num2,num3,num4,num5;
float avg;
cout<<"Enter marks of 5 subjects: ";
cin>>num1>>num2>>num3>>num4>>num5;
avg=(num1+num2+num3+num4+num5)/5;
if (avg>=50)
cout<<"Pass";
else
cout<<"Fail";
getch();
}
```

Program to demonstrate the use of if else statement

Computer Science

When the above program is executed, it will prompt the user to enter the marks of 5 subjects. Then it calculates the average and checks the condition if it is greater than or equal to 50 then it will print the output Pass. Otherwise it will print the output Fail.

Q5. What is the purpose and structure of if else statement? Explain with the help of examples.

Ans. Structure of the Statement

The **if else** statement is a two statement in which one or some of the two statements is executed. The **if else** statement is also called **two-way selection statement.**

The **if else** statement has the following general form **Syntax.**

if (condition)

{

Block of statements

}

else

{

Block of statements

}

Computer Science

When it does statement is executed, the condition is executed.

If the condition is true then the block of statements following it will be executed and the block of statements following else will be skipped.

Computer Science

If the condition is false then the block of statements following else will be executed.

After the execution of the statement is completed, the next statement after the statement is executed.

Ans. Use of Statement (Example)

Program 1: The program to find the average and pass fail the average student (example).

```
#include<iostream.h>
#include<conio.h>
void main()
{
int num1,num2,num3,num4,num5;
float avg;
cout<<"Enter marks of 5 subjects: ";
cin>>num1>>num2>>num3>>num4>>num5;
avg=(num1+num2+num3+num4+num5)/5;
if (avg>=50)
cout<<"Pass";
else
cout<<"Fail";
getch();
}
```

Program to demonstrate the use of if else statement

Computer Science

When the above program is executed, it will prompt the user to enter the marks of 5 subjects. Then it calculates the average and checks the condition if it is greater than or equal to 50 then it will print the output Pass. Otherwise it will print the output Fail.

Q6. What is the purpose and structure of if else statement? Explain with the help of examples.

Ans. Structure of the Statement

The **if else** statement is a two statement in which one or some of the two statements is executed. The **if else** statement is also called **two-way selection statement.**

The **if else** statement has the following general form **Syntax.**

if (condition)

{

Block of statements

}

else

{

Block of statements to be executed

When value of the condition is true

}

Computer Science

When it does statement is executed, the condition is executed. If the condition is true then the block of statements following it will be executed and the block of statements following else will be skipped.

Computer Science

If the condition is false then the block of statements following else will be executed.

After the execution of the statement is completed, the next statement after the statement is executed.

Ans. Use of Statement (Example)

Program 1: The program to find the average and pass fail the average student (example).

```
#include<iostream.h>
#include<conio.h>
void main()
{
int num1,num2,num3,num4,num5;
float avg;
cout<<"Enter marks of 5 subjects: ";
cin>>num1>>num2>>num3>>num4>>num5;
avg=(num1+num2+num3+num4+num5)/5;
if (avg>=50)
cout<<"Pass";
else
cout<<"Fail";
getch();
}
```

Program to demonstrate the use of if else statement

Computer Science

When the above program is executed, it will prompt the user to enter the marks of 5 subjects. Then it calculates the average and checks the condition if it is greater than or equal to 50 then it will print the output Pass. Otherwise it will print the output Fail.

Q7. What is the purpose and structure of if else statement? Explain with the help of examples.

Ans. Structure of the Statement

The **if else** statement is a two statement in which one or some of the two statements is executed. The **if else** statement is also called **two-way selection statement.**

The **if else** statement has the following general form **Syntax.**

if (condition)

{

Block of statements

}

else

{

Block of statements to be executed

When value of the condition is true

}

Computer Science

When it does statement is executed, the condition is executed. If the condition is true then the block of statements following it will be executed and the block of statements following else will be skipped.

Computer Science

If the condition is false then the block of statements following else will be executed.

After the execution of the statement is completed, the next statement after the statement is executed.

Ans. Use of Statement (Example)

Program 1: The program to find the average and pass fail the average student (example).

```
#include<iostream.h>
#include<conio.h>
void main()
{
int num1,num2,num3,num4,num5;
float avg;
cout<<"Enter marks of 5 subjects: ";
cin>>num1>>num2>>num3>>num4>>num5;
avg=(num1+num2+num3+num4+num5)/5;
if (avg>=50)
cout<<"Pass";
else
cout<<"Fail";
getch();
}
```

Program to demonstrate the use of if else statement

Computer Science

When the above program is executed, it will prompt the user to enter the marks of 5 subjects. Then it calculates the average and checks the condition if it is greater than or equal to 50 then it will print the output Pass. Otherwise it will print the output Fail.

Q8. What is the purpose and structure of if else statement? Explain with the help of examples.

Ans. Structure of the Statement

The **if else** statement is a two statement in which one or some of the two statements is executed. The **if else** statement is also called **two-way selection statement.**

The **if else** statement has the following general form **Syntax.**

if (condition)

{

Block of statements

}

else

{

Block of statements to be executed

When value of the condition is true

}

Computer Science

When it does statement is executed, the condition is executed. If the condition is true then the block of statements following it will be executed and the block of statements following else will be skipped.

Computer Science

If the condition is false then the block of statements following else will be executed.

After the execution of the statement is completed, the next statement after the statement is executed.

Ans. Use of Statement (Example)

Program 1: The program to find the average and pass fail the average student (example).

```
#include<iostream.h>
#include<conio.h>
void main()
{
int num1,num2,num3,num4,num5;
float avg;
cout<<"Enter marks of 5 subjects: ";
cin>>num1>>num2>>num3>>num4>>num5;
avg=(num1+num2+num3+num4+num5)/5;
if (avg>=50)
cout<<"Pass";
else
cout<<"Fail";
getch();
}
```

Program to demonstrate the use of if else statement

Computer Science

When the above program is executed, it will prompt the user to enter the marks of 5 subjects. Then it calculates the average and checks the condition if it is greater than or equal to 50 then it will print the output Pass. Otherwise it will print the output Fail.

Q9. What is the purpose and structure of if else statement? Explain with the help of examples.

Ans. Structure of the Statement

The **if else** statement is a two statement in which one or some of the two statements is executed. The **if else** statement is also called **two-way selection statement.**

The **if else** statement has the following general form **Syntax.**

if (condition)

{

Block of statements

}

else

{

Block of statements to be executed

When value of the condition is true

}

Computer Science

When it does statement is executed, the condition is executed. If the condition is true then the block of statements following it will be executed and the block of statements following else will be skipped.

Computer Science

If the condition is false then the block of statements following else will be executed.

After the execution of the statement is completed, the next statement after the statement is executed.

Ans. Use of Statement (Example)

Program 1: The program to find the average and pass fail the average student (example).

```
#include<iostream.h>
#include<conio.h>
void main()
{
int num1,num2,num3,num4,num5;
float avg;
cout<<"Enter marks of 5 subjects: ";
cin>>num1>>num2>>num3>>num4>>num5;
avg=(num1+num2+num3+num4+num5)/5;
if (avg>=50)
cout<<"Pass";
else
cout<<"Fail";
getch();
}
```

Program to demonstrate the use of if else statement

Computer Science

When the above program is executed, it will prompt the user to enter the marks of 5 subjects. Then it calculates the average and checks the condition if it is greater than or equal to 50 then it will print the output Pass. Otherwise it will print the output Fail.

Q10. What is the purpose and structure of if else statement? Explain with the help of examples.

Ans. Structure of the Statement

The **if else** statement is a two statement in which one or some of the two statements is executed. The **if else** statement is also called **two-way selection statement.**

The **if else** statement has the following general form **Syntax.**

if (condition)

{

Block of statements

}

else

{

Block of statements to be executed

When value of the condition is true

}

Computer Science

When it does statement is executed, the condition is executed. If the condition is true then the block of statements following it will be executed and the block of statements following else will be skipped.

Computer Science

If the condition is false then the block of statements following else will be executed.

After the execution of the statement is completed, the next statement after the statement is executed.

Ans. Use of Statement (Example)

Program 1: The program to find the average and pass fail the average student (example).

```
#include<iostream.h>
#include<conio.h>
void main()
{
int num1,num2,num3,num4,num5;
float avg;
cout<<"Enter marks of 5 subjects: ";
cin>>num1>>num2>>num3>>num4>>num5;
avg=(num1+num2+num3+num4+num5)/5;
if (avg>=50)
cout<<"Pass";
else
cout<<"Fail";
getch();
}
```

Program to demonstrate the use of if else statement

Computer Science

When the above program is executed, it will prompt the user to enter the marks of 5 subjects. Then it calculates the average and checks the condition if it is greater than or equal to 50 then it will print the output Pass. Otherwise it will print the output Fail.

Q11. What is the purpose and structure of if else statement? Explain with the help of examples.

Ans. Structure of the Statement

The **if else** statement is a two statement in which one or some of the two statements is executed. The **if else** statement is also called **two-way selection statement.**

The **if else** statement has the following general form **Syntax.**

if (condition)

{

Block of statements

}

else

{

Block of statements to be executed

When value of the condition is true

}

Computer Science

When it does statement is executed, the condition is executed. If the condition is true then the block of statements following it will be executed and the block of statements following else will be skipped.

Computer Science

If the condition is false then the block of statements following else will be executed.

After the execution of the statement is completed, the next statement after the statement is executed.

Ans. Use of Statement (Example)

Program 1: The program to find the average and pass fail the average student (example).

```
#include<iostream.h>
#include<conio.h>
void main()
{
int num1,num2,num3,num4,num5;
float avg;
cout<<"Enter marks of 5 subjects: ";
cin>>num1>>num2>>num3>>num4>>num5;
avg=(num1+num2+num3+num4+num5)/5;
if (avg>=50)
cout<<"Pass";
else
cout<<"Fail";
getch();
}
```

Program to demonstrate the use of if else statement

Computer Science

When the above program is executed, it will prompt the user to enter the marks of 5 subjects. Then it calculates the average and checks the condition if it is greater than or equal to 50 then it will print the output Pass. Otherwise it will print the output Fail.

Q12. What is the purpose and structure of if else statement? Explain with the help of examples.

Ans. Structure of the Statement

The **if else** statement is a two statement in which one or some of the two statements is executed. The **if else** statement is also called **two-way selection statement.**

The **if else** statement has the following general form **Syntax.**

if (condition)

{

Block of statements

}

else

{

Block of statements to be executed

When value of the condition is true

}

Computer Science

When it does statement is executed, the condition is executed. If the condition is true then the block of statements following it will be executed and the block of statements following else will be skipped.

Computer Science

If the condition is false then the block of statements following else will be executed.

After the execution of the statement is completed, the next statement after the statement is executed.

Ans. Use of Statement (Example)

Program 1: The program to find the average and pass fail the average student (example).

```
#include<iostream.h>
#include<conio.h>
void main()
{
int num1,num2,num3,num4,num5;
float avg;
cout<<"Enter marks of 5 subjects: ";
cin>>num1>>num2>>num3>>num4>>num5;
avg=(num1+num2+num3+num4+num5)/5;
if (avg>=50)
cout<<"Pass";
else
cout<<"Fail";
getch();
}
```

Program to demonstrate the use of if else statement

Computer Science

When the above program is executed, it will prompt the user to enter the marks of 5 subjects. Then it calculates the average and checks the condition if it is greater than or equal to 50 then it will print the output Pass. Otherwise it will print the output Fail.

Q13. What is the purpose and structure of if else statement? Explain with the help of examples.

Ans. Structure of the Statement

The **if else** statement is a two statement in which one or some of the two statements is executed. The **if else** statement is also called **two-way selection statement.**

The **if else** statement has the following general form **Syntax.**

if (condition)

{

Block of statements

}

else

{

Block of statements to be executed

When value of the condition is true

}

Computer Science

When it does statement is executed, the condition is executed. If the condition is true then the block of statements following it will be executed and the block of statements following else will be skipped.

Computer Science

If the condition is false then the block of statements following else will be executed.

After the execution of the statement is completed, the next statement after the statement is executed.

Ans. Use of Statement (Example)

Program 1: The program to find the average and pass fail the average student (example).

```
#include<iostream.h>
#include<conio.h>
void main()
{
int num1,num2,num3,num4,num5;
float avg;
cout<<"Enter marks of 5 subjects: ";
cin>>num1>>num2>>num3>>num4>>num5;
avg=(num1+num2+num3+num4+num5)/5;
if (avg>=50)
cout<<"Pass";
else
cout<<"Fail";
getch();
}
```

Program to demonstrate the use of if else statement

Computer Science

When the above program is executed, it will prompt the user to enter the marks of 5 subjects. Then it calculates the average and checks the condition if it is greater than or equal to 50 then it will print the output Pass. Otherwise it will print the output Fail.

Q14. What is the purpose and structure of if else statement? Explain with the help of examples.

Ans. Structure of the Statement

The **if else** statement is a two statement in which one or some of the two statements is executed. The **if else** statement is also called **two-way selection statement.**

The **if else** statement has the following general form **Syntax.**

if (condition)

{

Block of statements

}

else

{

Block of statements to be executed

When value of the condition is true

}

Computer Science

When it does statement is executed, the condition is executed. If the condition is true then the block of statements following it will be executed and the block of statements following else will be skipped.

Computer Science

If the condition is false then the block of statements following else will be executed.

After the execution of the statement is completed, the next statement after the statement is executed.

Ans. Use of Statement (Example)

Program 1: The program to find the average and pass fail the average student (example).

```
#include<iostream.h>
#include<conio.h>
void main()
{
int num1,num2,num3,num4,num5;
float avg;
cout<<"Enter marks of 5 subjects: ";
cin>>num1>>num2>>num3>>num4>>num5;
avg=(num1+num2+num3+num4+num5)/5;
if (avg>=50)
cout<<"Pass";
else
cout<<"Fail";
getch();
}
```

Program to demonstrate the use of if else statement

Computer Science

When the above program is executed, it will prompt the user to enter the marks of 5 subjects. Then it calculates the average and checks the condition if it is greater than or equal to 50 then it will print the output Pass. Otherwise it will print the output Fail.

Q15. What is the purpose and structure of if else statement? Explain with the help of examples.

Ans. Structure of the Statement

The **if else** statement is a two statement in which one or some of the two statements is executed. The **if else** statement is also called **two-way selection statement.**

The **if else** statement has the following general form **Syntax.**

if (condition)

{

Block of statements

}

else

{

Block of statements to be executed

When value of the condition is true

}

Computer Science

When it does statement is executed, the condition is executed. If the condition is true then the block of statements following it will be executed and the block of statements following else will be skipped.

Computer Science

If the condition is false then the block of statements following else will be executed.

After the execution of the statement is completed, the next statement after the statement is executed.

Ans. Use of Statement (Example)

Program 1: The program to find the average and pass fail the average student (example).

```
#include<iostream.h>
#include<conio.h>
void main()
{
int num1,num2,num3,num4,num5;
float avg;
cout<<"Enter marks of 5 subjects: ";
cin>>num1>>num2>>num3>>num4>>num5;
avg=(num1+num2+num3+num4+num5)/5;
if (avg>=50)
cout<<"Pass";
else
cout<<"Fail";
getch();
}
```

Program to demonstrate the use of if else statement

Computer Science

When the above program is executed, it will prompt the user to enter the marks of 5 subjects. Then it calculates the average and checks the condition if it is greater than or equal to 50 then it will print the output Pass. Otherwise it will print the output Fail.

Q16. What is the purpose and structure of if else statement? Explain with the help of examples.

Ans. Structure of the Statement

The **if else** statement is a two statement in which one or some of the two statements is executed. The **if else** statement is also called **two-way selection statement.**

The **if else** statement has the following general form **Syntax.**

if (condition)

{

Block of statements

}

else

{

Block of statements to be executed

When value of the condition is true

}

Computer Science

When it does statement is executed, the condition is executed. If the condition is true then the block of statements following it will be executed and the block of statements following else will be skipped.

Computer Science

If the condition is false then the block of statements following else will be executed.

After the execution of the statement is completed, the next statement after the statement is executed.

Ans. Use of Statement (Example)

Program 1: The program to find the average and pass fail the average student (example).

```
#include<iostream.h>
#include<conio.h>
void main()
{
int num1,num2,num3,num4,num5;
float avg;
cout<<"Enter marks of 5 subjects: ";
cin>>num1>>num2>>num3>>num4>>num5;
avg=(num1+num2+num3+num4+num5)/5;
if (avg>=50)
cout<<"Pass";
else
cout<<"Fail";
getch();
}
```

Program to demonstrate the use of if else statement

Computer Science

When the above program is executed, it will prompt the user to enter the marks of 5 subjects. Then it calculates the average and checks the condition if it is greater than or equal to 50 then it will print the output Pass. Otherwise it will print the output Fail.

Q17. What is the purpose and structure of if else statement? Explain with the help of examples.

Ans. Structure of the Statement

The **if else** statement is a two statement in which one or some of the two statements is executed. The **if else** statement is also called **two-way selection statement.**

The **if else** statement has the following general form **Syntax.**

if (condition)

{

Block of statements

}

else

{

Block of statements to be executed

When value of the condition is true

}

Computer Science

When it does statement is executed, the condition is executed. If the condition is true then the block of statements following it will be executed and the block of statements following else will be skipped.

Computer Science

If the condition is false then the block of statements following else will be executed.

After the execution of the statement is completed, the next statement after the statement is executed.

Ans. Use of Statement (Example)

Program 1: The program to find the average and pass fail the average student (example).

```
#include<iostream.h>
#include<conio.h>
void main()
{
int num1,num2,num3,num4,num5;
float avg;
cout<<"Enter marks of 5 subjects: ";
cin>>num1>>num2>>num3>>num4>>num5;
avg=(num1+num2+num3+num4+num5)/5;
if (avg>=50)
cout<<"Pass";
else
cout<<"Fail";
getch();
}
```

Program to demonstrate the use of if else statement

Computer Science

When the above program is executed, it will prompt the user to enter the marks of 5 subjects. Then it calculates the average and checks the condition if it is greater than or equal to 50 then it will print the output Pass. Otherwise it will print the output Fail.

Q18. What is the purpose and structure of if else statement? Explain with the help of examples.

Ans. Structure of the Statement

The **if else** statement is a two statement in which one or some of the two statements is executed. The **if else** statement is also called **two-way selection statement.**

The **if else** statement has the following general form **Syntax.**

if (condition)

{

Block of statements

}

else

{

Block of statements to be executed

When value of the condition is true

}

Computer Science

When it does statement is executed, the condition is executed. If the condition is true then the block of statements following it will be executed and the block of statements following else will be skipped.

Computer Science

If the condition is false then the block of statements following else will be executed.

After the execution of the statement is completed, the next statement after the statement is executed.

Ans. Use of Statement (Example)

Program 1: The program to find the average and pass fail the average student (example).

```
#include<iostream.h>
#include<conio.h>
void main()
{
int num1,num2,num3,num4,num5;
float avg;
cout<<"Enter marks of 5 subjects: ";
cin>>num1>>num2>>num3>>num4>>num5;
avg=(num1+num2+num3+num4+num5)/5;
if (avg>=50)
cout<<"Pass";
else
cout<<"Fail";
getch();
}
```

Program to demonstrate the use of if else statement

Computer Science

When the above program is executed, it will prompt the user to enter the marks of 5 subjects. Then it calculates the average and checks the condition if it is greater than or equal to 50 then it will print the output Pass. Otherwise it will print the output Fail.

Q19. What is the purpose and structure of if else statement? Explain with the help of examples.

Ans. Structure of the Statement

The **if else** statement is a two statement in which one or some of the two statements is executed. The **if else** statement is also called **two-way selection statement.**

The **if else** statement has the following general form **Syntax.**

if (condition)

{

Block of statements

}

else

{

Block of statements to be executed

When value of the condition is true

}

Computer Science

When it does statement is executed, the condition is executed. If the condition is true then the block of statements following it will be executed and the block of statements following else will be skipped.

Computer Science

If the condition is false then the block of statements following else will be executed.

After the execution of the statement is completed, the next statement after the statement is executed.

Ans. Use of Statement (Example)

Program 1: The program to find the average and pass fail the average student (example).

```
#include<iostream.h>
#include<conio.h>
void main()
{
int num1,num2,num3,num4,num5;
float avg;
cout<<"Enter marks of 5 subjects: ";
cin>>num1>>num2>>num3>>num4>>num5;
avg=(num1+num2+num3+num4+num5)/5;
if (avg>=50)
cout<<"Pass";
else
cout<<"Fail";
getch();
}
```

Program to demonstrate the use of if else statement

Computer Science

When the above program is executed, it will prompt the user to enter the marks of 5 subjects. Then it calculates the average and checks the condition if it is greater than or equal to 50 then it will print the output Pass. Otherwise it will print the output Fail.

Q20. What is the purpose and structure of if else statement? Explain with the help of examples.

Ans. Structure of the Statement

The **if else** statement is a two statement in which one or some of the two statements is executed. The **if else** statement is also called **two-way selection statement.**

The **if else** statement has the following general form **Syntax.**

if (condition)

{

Block of statements

}

else

{

Block of statements to be executed

When value of the condition is true

}

Computer Science

When it does statement is executed, the condition is executed. If the condition is true then the block of statements following it will be executed and the block of statements following else will be skipped.

Computer Science

If the condition is false then the block of statements following else will be executed.

After the execution of the statement is completed, the next statement after the statement is executed.

Ans. Use of Statement (Example)

Program 1: The program to find the average and pass fail the average student (example).

```
#include<iostream.h>
#include<conio.h>
void main()
{
int num1,num2,num3,num4,num5;
float avg;
cout<<"Enter marks of 5 subjects: ";
cin>>num1>>num2>>num3>>num4>>num5;
avg=(num1+num2+num3+num4+num5)/5;
if (avg>=50)
cout<<"Pass";
else
cout<<"Fail";
getch();
}
```

Program to demonstrate the use of if else statement

Computer Science

When the above program is executed, it will prompt the user to enter the marks of 5 subjects. Then it calculates the average and checks the condition if it is greater than or equal to 50 then it will print the output Pass. Otherwise it will print the output Fail.

Q21. What is the purpose and structure of if else statement? Explain with the help of examples.

Ans. Structure of the Statement

The **if else** statement is a two statement in which one or some of the two statements is executed. The **if else** statement is also called **two-way selection statement.**

The **if else** statement has the following general form **Syntax.**

if (condition)

{

Block of statements

}

else

{

Block of statements to be executed

When value of the condition is true

}

Computer Science

When it does statement is executed, the condition is executed. If the condition is true then the block of statements following it will be executed and the block of statements following else will be skipped.

Computer Science

If the condition is false then the block of statements following else will be executed.

After the execution of the statement is completed, the next statement after the statement is executed.

Ans. Use of Statement (Example)

Program 1: The program to find the average and pass fail the average student (example).

```
#include<iostream.h>
#include<conio.h>
void main()
{
int num1,num2,num3,num4,num5;
float avg;
cout<<"Enter marks of 5 subjects: ";
cin>>num1>>num2>>num3>>num4>>num5;
avg=(num1+num2+num3+num4+num5)/5;
if (avg>=50)
cout<<"Pass";
else
cout<<"Fail";
getch();
}
```

Program to demonstrate the use of if else statement

Computer Science

When the above program is executed, it will prompt the user to enter the marks of 5 subjects. Then it calculates the average and checks the condition if it is greater than or equal to 50 then it will print the output Pass. Otherwise it will print the output Fail.

Q22. What is the purpose and structure of if else statement? Explain with the help of examples.

Ans. Structure of the Statement

The **if else** statement is a two statement in which one or some of the two statements is executed. The **if else** statement is also called **two-way selection statement.**

The **if else** statement has the following general form **Syntax.**

if (condition)

{

Block of statements

}

else

{

Block of statements to be executed

When value of the condition is true

}

Computer Science

When it does statement is executed, the condition is executed. If the condition is true then the block of statements following it will be executed and the block of statements following else will be skipped.

Computer Science

If the condition is false then the block of statements following else will be executed.

After the execution of the statement is completed, the next statement after the statement is executed.

Ans. Use of Statement (Example)

Program 1: The program to find the average and pass fail the average student (example).

```
#include<iostream.h>
#include<conio.h>
void main()
{
int num1,num2,num3,num4,num5;
float avg;
cout<<"Enter marks of 5 subjects: ";
cin>>num1>>num2>>num3>>num4>>num5;
avg=(num1+num2+num3+num4+num5)/5;
if (avg>=50)
cout<<"Pass";
else
cout<<"Fail";
getch();
}
```

Program to demonstrate the use of if else statement

Computer Science

When the above program is executed, it will prompt the user to enter the marks of 5 subjects. Then it calculates the average and checks the condition if it is greater than or equal to 50 then it will print the output Pass. Otherwise it will print the output Fail.

Q23. What is the purpose and structure of if else statement? Explain with the help of examples.

Ans. Structure of the Statement

The **if else** statement is a two statement in which one or some of the two statements is executed. The **if else** statement is also called **two-way selection statement.**

The **if else** statement has the following general form **Syntax.**

if (condition)

{

Block of statements

}

else

{

Block of statements to be executed

When value of the condition is true

}

Computer Science

When it does statement is executed, the condition is executed. If the condition is true then the block of statements following it will be executed and the block of statements following else will be skipped.

Computer Science

If the condition is false then the block of statements following else will be executed.

After the execution of the statement is completed, the next statement after the statement is executed.

Ans. Use of Statement (Example)

Program 1: The program to find the average and pass fail the average student (example).

```
#include<iostream.h>
#include<conio.h>
void main()
{
int num1,num2,num3,num4,num5;
float avg;
cout<<"Enter marks of 5 subjects: ";
cin>>num1>>num2>>num3>>num4>>num5;
avg=(num1+num2+num3+num4+num5)/5;
if (avg>=50)
cout<<"Pass";
else
cout<<"Fail";
getch();
}
```

Program to demonstrate the use of if else statement

Computer Science

When the above program is executed, it will prompt the user to enter the marks of 5 subjects. Then it calculates the average and checks the condition if it is greater than or equal to 50 then it will print the output Pass. Otherwise it will print the output Fail.

Q24. What is the purpose and structure of if else statement? Explain with the help of examples.

Ans. Structure of the Statement

The **if else** statement is a two statement in which one or some of the two statements is executed. The **if else** statement is also called **two-way selection statement.**

The **if else** statement has the following general form **Syntax.**

if (condition)

{

Block of statements

}

else

{

Block of statements to be executed

When value of the condition is true

}

Computer Science

When it does statement is executed, the condition is executed. If the condition is true then the block of statements following it will be executed and the block of statements following else will be skipped.

Computer Science

If the condition is false then the block of statements following else will be executed.

After the execution of the statement is completed, the next statement after the statement is executed.

Ans. Use of Statement (Example)

Program 1: The program to find the average and pass fail the average student (example).

```
#include<iostream.h>
#include<conio.h>
void main()
{
int num1,num2,num3,num4,num5;
float avg;
cout<<"Enter marks of 5 subjects: ";
cin>>num1>>num2>>num3>>num4>>num5;
avg=(num1+num2+num3+num4+num5)/5;
if (avg>=50)
cout<<"Pass";
else
cout<<"Fail";
getch();
}
```

Program to demonstrate the use of if else statement

Computer Science

When the above program is executed, it will prompt the user to enter the marks of 5 subjects. Then it calculates the average and checks the condition if it is greater than or equal to 50 then it will print the output Pass. Otherwise it will print the output Fail.

Q25. What is the purpose and structure of if else statement? Explain with the help of examples.

Ans. Structure of the Statement

The **if else** statement is a two statement in which one or some of the two statements is executed. The **if else** statement is also called **two-way selection statement.**

The **if else** statement has the following general form **Syntax.**

if (condition)

{

Block of statements

}

else

{

Block of statements to be executed

When value of the condition is true

}

Computer Science

When it does statement is executed, the condition is executed. If the condition is true then the block of statements following it will be executed and the block of statements following else will be skipped.

Computer Science

If the condition is false then the block of statements following else will be executed.

After the execution of the statement is completed, the next statement after the statement is executed.

Ans. Use of Statement (Example)

Program 1: The program to find the average and pass fail the average student (example).

```
#include<iostream.h>
#include<conio.h>
void main()
{
int num1,num2,num3,num4,num5;
float avg;
cout<<"Enter marks of 5 subjects: ";
cin>>num1>>num2>>num3>>num4>>num5;
avg=(num1+num2+num3+num4+num5)/5;
if (avg>=50)
cout<<"Pass";
else
cout<<"Fail";
getch();
}
```

Program to demonstrate the use of if else statement

Computer Science

When the above program is executed, it will prompt the user to enter the marks of 5 subjects. Then it calculates the average and checks the condition if it is greater than or equal to 50 then it will print the output Pass. Otherwise it will print the output Fail.

Q26. What is the purpose and structure of if else statement? Explain with the help of examples.

Ans. Structure of the Statement

The **if else** statement is a two statement in which one or some of the two statements is executed. The **if else** statement is also called **two-way selection statement.**

The **if else** statement has the following general form **Syntax.**

if (condition)

{

Block of statements

}

else

{

Block of statements to be executed

When value of the condition is true

}

Computer Science

When it does statement is executed, the condition is executed. If the condition is true then the block of statements following it will be executed and the block of statements following else will be skipped.

Computer Science

If the condition is false then the block of statements following else will be executed.

After the execution of the statement is completed, the next statement after the statement is executed.

Ans. Use of Statement (Example)

Program 1: The program to find the average and pass fail the average student (example).

```
#include<iostream.h>
#include<conio.h>
void main()
{
int num1,num2,num3,num4,num5;
float avg;
cout<<"Enter marks of 5 subjects: ";
cin>>num1>>num2>>num3>>num4>>num5;
avg=(num1+num2+num3+num4+num5)/5;
if (avg>=50)
cout<<"Pass";
else
cout<<"Fail";
getch();
}
```

Program to demonstrate the use of if else statement

Computer Science

When the above program is executed, it will prompt the user to enter the marks of 5 subjects. Then it calculates the average and checks the condition if it is greater than or equal to 50 then it will print the output Pass. Otherwise it will print the output Fail.

Q27. What is the purpose and structure of if else statement? Explain with the help of examples.

Ans. Structure of the Statement

The **if else** statement is a two statement in which one or some of the two statements is executed. The **if else** statement is also called **two-way selection statement.**

The **if else** statement has the following general form **Syntax.**

if (condition)

{

Block of statements

}

else

{

Block of statements to be executed

When value of the condition is true

}

Computer Science

When it does statement is executed, the condition is executed. If the condition is true then the block of statements following it will be executed and the block of statements following else will be skipped.

Computer Science

If the condition is false then the block of statements following else will be executed.

After the execution of the statement is completed, the next statement after the statement is executed.

Ans. Use of Statement (Example)

Program 1: The program to find the average and pass fail the average student (example).

```
#include<iostream.h>
#include<conio.h>
void main()
{
int num1,num2,num3,num4,num5;
float avg;
cout<<"Enter marks of 5 subjects: ";
cin>>num1>>num2>>num3>>num4>>num5;
avg=(num1+num2+num3+num4+num5)/5;
if (avg>=50)
cout<<"Pass";
else
cout<<"Fail";
getch();
}
```

Program to demonstrate the use of if else statement

Computer Science

When the above program is executed, it will prompt the user to enter the marks of 5 subjects. Then it calculates the average and checks the condition if it is greater than or equal to 50 then it will print the output Pass. Otherwise it will print the output Fail.

Q28. What is the purpose and structure of if else statement? Explain with the help of examples.

Ans. Structure of the Statement

The **if else** statement is a two statement in which one or some of the two statements is executed. The **if else** statement is also called **two-way selection statement.**

The **if else** statement has the following general form **Syntax.**

if (condition)

{

Block of statements

}

else

{

Block of statements to be executed

When value of the condition is true

}

Computer Science

When it does statement is executed, the condition is executed. If the condition is true then the block of statements following it will be executed and the block of statements following else will be skipped.

Computer Science

If the condition is false then the block of statements following else will be executed.

After the execution of the statement is completed, the next statement after the statement is executed.

Ans. Use of Statement (Example)

Program 1: The program to find the average and pass fail the average student (example).

```
#include<iostream.h>
#include<conio.h>
void main()
{
int num1,num2,num3,num4,num5;
float avg;
cout<<"Enter marks of 5 subjects: ";
cin>>num1>>num2>>num3>>num4>>num5;
avg=(num1+num2+num3+num4+num5)/5;
if (avg>=50)
cout<<"Pass";
else
cout<<"Fail";
getch();
}
```

Program to demonstrate the use of if else statement

Computer Science

When the above program is executed, it will prompt the user to enter the marks of 5 subjects. Then it calculates the average and checks the condition if it is greater than or equal to 50 then it will print the output Pass. Otherwise it will print the output Fail.

Q29. What is the purpose and structure of if else statement? Explain with the help of examples.

Ans. Structure of the Statement

The **if else** statement is a two statement in which one or some of the two statements is executed. The **if else** statement is also called **two-way selection statement.**

The **if else** statement has the following general form **Syntax.**

if (condition)

{

Block of statements

}

else

{

Block of statements to be executed

When value of the condition is true

}

Computer Science

When it does statement is executed, the condition is executed. If the condition is true then the block of statements following it will be executed and the block of statements following else will be skipped.

Computer Science

If the condition is false then the block of statements following else will be executed.

After the execution of the statement is completed, the next statement after the statement is executed.

Ans. Use of Statement (Example)

Program 1: The program to find the average and pass fail the average student (example).

```
#include<iostream.h>
#include<conio.h>
void main()
{
int num1,num2,num3,num4,num5;
float avg;
cout<<"Enter marks of 5 subjects: ";
cin>>num1>>num2>>num3>>num4>>num5;
avg=(num1+num2+num3+num4+num5)/5;
if (avg>=50)
cout<<"Pass";
else
cout<<"Fail";
getch();
}
```

Program to demonstrate the use of if else statement

Computer Science

When the above program is executed, it will prompt the user to enter the marks of 5 subjects. Then it calculates the average and checks the condition if it is greater than or equal to 50 then it will print the output Pass. Otherwise it will print the output Fail.

Q30. What is the purpose and structure of if else statement? Explain with the help of examples.

Ans. Structure of the Statement

The **if else** statement is a two statement in which one or some of the two statements is executed. The **if else** statement is also called **two-way selection statement.**

The **if else** statement has the following general form **Syntax.**

if (condition)

{

Block of statements

}

else

{

**

EXERCISE

Q1. Select the best answer for the following MCQs.

1. **For which purpose if-else-if ladder is used in programming:**
   a. Looping
   b. Selection
   c. Sequencing
   d. None of these

2. **Which statement is suitable to use in a situation where there are only two possibilities to check a condition?**
   a. if statement
   b. if else if statement
   c. if else statement
   d. Switch statement

3. **Which statement can be used in place of switch statement?**
   a. if statement
   b. if else if statement
   c. if else statement
   d. Conditional operator

4. **Which statement can be used in place of conditional operator?**
   a. if statement
   b. if else statement
   c. if else if statement
   d. Switch statement

5. **Which statement is used to terminate the body of switch statement?**
   a. Default
   b. Continue
   c. Case
   d. Break

6. **Which of the following is a multiple selection statement?**
   a. if statement
   b. if else if statement
   c. if else if statement
   d. None of these

7. **Which of the selection structures tests only for equality?**
   a. if structure
   b. if else structure
   c. if else if statement
   d. Switch statement

8. **What will be printed when the following code is executed?**

```
int x=1;
switch(x)
{
    Case 1:
    Case2:
    Case 3:
    printf("x is a multiple number");
        break;
    default:
}
```

```
    break; // in case of x is 1
}
```

a. Value of x is 1
b. It is a positive number
c. x is a multiple number
d. It will give error

Answers

1. d	2. a	3. c	4. d
5. b	6. c	7. d	8. b

SHORT QUESTIONS

Q2. Give short answers to the following questions.

How many types of selection structures are there in C++? Name them.

There are **three** types of selection structures in C++.

1. **if statement**
2. **if else statement**
3. **Switch statement**

if statement

```
if (condition)
{
    Block of statements
}
```

Flow

```
{
    Block of statements
}
```

if else Selection Structure

The if else statement is used in situation where some code is to be executed if a condition is true and some other code is to be executed if the condition is false.

The **if else** statement has the following **general form / Syntax.**

If (condition)

```
{
    Block of statements
}
else
{
    Block of statements
}
```

Flow

```
{
    Block of statements
}
else
{
    Block of statements
}
```

3. Differentiate between else if and switch selection structures.

Ans. else if selection Structure:

The if else statement is used in situation where some code is to be executed if a condition is true and some other if else if the condition is false.

The if else statement has the following general form / Syntax.

If (condition)

```
{
    Block of statements
}
else
{
    Block of statements
}
```

Flow

```
{
    Block of statements
}
else
{
    Block of statements
}
```

4. What is nested selection structure?

Ans. Nested Selection Structure:

The selection structure that is within another selection structure is known as nested selection structure. In other words, if a selection structure is used as a statement in the true or the false part of another selection structure. This is also supported in C language. In C language, the general form of nested selection structure **if else, else if, switch** statement within another selection structure.

Switch (expression)

```
{
Case const 1:
        Statements
        Break;
Case const 2:
        Statements
        Break;
Default
        Statements
}
```

Flow

- When the program encounters switch statement, it looks at the value in the variable. It will then find the condition (of cases) that matches the value of the variable and execute the statements (or block of statements) associated with that condition (case).
- The control is then passed to the statement that is just after the closing brace } of the switch statement.
- If none of the conditions (of cases) matches the value of the variable, then the default statement is executed.

5. What is nested selection structure?

Ans. Nested Selection Structure:

The selection structure that is within another selection structure is known as nested selection structure. In other words, if a selection structure is used as a statement in the true or the false part of another selection structure. This is also supported in C language. In C language, the general form of nested selection structure **if else, else if, switch** statement within another selection structure.

Switch (expression)

```
{
Case const 1:
        Statements
        Break;
Case const 2:
        Statements
        Break;
Default
        Statements
}
```

Flow

- When the program encounters switch statement, it looks at the value in the variable. It will then find the condition (of cases) that matches the value of the variable and execute the statements (or block of statements) associated with that condition (case).
- The control is then passed to the statement that is just after the closing brace } of the switch statement.
- If none of the conditions (of cases) matches the value of the variable, then the default statement is executed.

6. What is nested selection structure?

Ans. Nested Selection Structure:

The selection structure that is within another selection structure is known as nested selection structure. In other words, if a selection structure is used as a statement in the true or the false part of another selection structure. This is also supported in C language. In C language, the general form of nested selection structure **if else, else if, switch** statement within another selection structure.

Switch (expression)

```
{
Case const 1:
        Statements
        Break;
Case const 2:
        Statements
        Break;
Default
        Statements
}
```

Flow

- When the program encounters switch statement, it looks at the value in the variable. It will then find the condition (of cases) that matches the value of the variable and execute the statements (or block of statements) associated with that condition (case).
- The control is then passed to the statement that is just after the closing brace } of the switch statement.
- If none of the conditions (of cases) matches the value of the variable, then the default statement is executed.

7. Write a program that reads two integers and finds the greater of the two integers.

```
#include<iostream.h>
#include<conio.h>
void main()
{
    int a,b;
    clrscr();
    cout<<"Enter two integers: ";
    cin>>a>>b;
    if(a>b)
        cout<<"\n"<<a<<" is greater than "<<b;
    else if(b>a)
        cout<<"\n"<<b<<" is greater than "<<a;
    else
        cout<<"\nBoth integers are equal";
    getch();
}
```

Program to find greater of two integers

8. Write the following statement using if else statement.

If you are late go to the car.

```
Else  Parking lot
      Go to
      Car
Else
      Go to
      Work
```

9. Write the following statement using conditional operator.

```
Print 10
Print 20
Else
      Print 30
Int a=10, b=20, c=30;
```

10. What will be the output of the following code?

```
int x=2, count=0;
switch (x) {case 2:
if (x>0)
```

```
{
    count++;
    cout<<"x is positive";
    break;
}
case 3:
    count--;
    cout<<"x is negative";
    break;
default:
    cout<<"x is zero";
}
```

EXTENDED QUESTIONS

Q1. What is control structure? Explain conditional control structures with examples.

Ans. Control Structure

In a computer program language, a control statement is an instruction which determines the sequence or direction of instructions in a program.

Control structures are used in programs to implement decisions.

Conditional control structure

Conditional Statement

A conditional statement is an instruction in a programming language that executes or jumps to different instructions depending on whether a specified fact the condition is evaluated and then based on the result of that, a particular statement or a set of statements is executed.

Conditional statements in C/C++ language are **if else, else if** and **switch** statements.

Structure of if Statements

The if statement has the following general form.

If (condition)

```
{
    Block of statements
}
```

Use of if Statement

Example

Program 1: In the program to flag, demonstrates the use of if statement

```
#include<iostream.h>
#include<conio.h>
void main()
{
    int number;
    cout<<"Enter a number: ";
    cin>>number;
    if(number<0)
        cout<<"\nYou entered a negative number";
    if(number>0)
        cout<<"\nYou entered a positive number";
    getch();
}
```

Program to find whether the no is +ve or negative

Structure of if else Statement

The if else statement is used in situation where some code is to be executed if a condition is true and some other code is to be executed if the condition is false.

The **if else** statement has the following general form.

If (condition)

```
{
    Block of statements
}
else
{
    Block of statements
}
```

Flow

```
{
    Block of statements
}
else
{
    Block of statements
}
```

- If a single statement is to be executed after the if else then braces are not necessary.

Structure of if else if Statement

The else if is a type of conditional statement that contains code that the computer executes if the previous conditional statement is false and a specific condition is true. It starts with the keyword else if.

If (condition 1)

```
{
    Block of statements
}
else if (condition 2)
{
    Block of statements
}
else if (condition n)
{
    Block of statements
}
```

Flow

```
{
    Block of statements to be executed
}
else if (condition 2)
{
    Block of statements to be executed
}
else if (condition n)
{
    Block of statements to be executed
}
```

What more of the conditions it is true

- When the statement is executed, condition 1 is evaluated. If it is true then the statements associated with condition 1 are executed. If it is false, the condition 2 is evaluated.
- If any condition is true then the following block of statements is executed.
- If none of the conditions (of cases) is true then the block of statements following else is executed and control exits.
- If a single statement is to be executed after if, else if or else instead of a set of statements then braces are not necessary.

Switch Statement

The **switch** statement has the following general form.

Switch (expression)

```
{
Case const1 :
        Statements
Case const 2:
        Statements
        Break;
.
.
.
Default
        Statements
}
```

Purpose of switch statement

- The switch statement is similar to the else if statement in C++ and other multiple choice programs and also executes in the same way.

- A switch statement is allowed to use a variable within the parentheses instead of expression based on which intended code is executed.
- The purpose of break statement is to exit the body of the switch statement after the code has been executed. Without the break statement, the code will continue executing the rest of the switch statement.
- The default statement is optional and specifies the code that is executed if no other cases do not evaluate to true. If it is not used then the control will exit from the body of the switch statement if the other statements in the switch do not match the value of the condition.
- The statement(s) inside each of "case:" is/are not "block".
- **Example:** The program to flag, uses a number of case changes as shift variable.

```
#include<iostream.h>
#include<conio.h>
void main()
{
    int number;
    cout<<"Enter a number: ";
    cin>>number;
    switch(number)
    {
        case 1:
            cout<<"\nYou entered 1";
            break;
        case 2:
            cout<<"\nYou entered 2";
            break;
        case 3:
            cout<<"\nYou entered 3";
            break;
        default:
            cout<<"\nYou entered a number other than 1, 2 or 3";
    }
    getch();
}
```

Program to demonstrate the use of switch statement

- When the program is executed, the switch variable must have an integer value. The value of switch variable is compared with the constant values following the case statements. If a match is found then, control is transferred to the statement(s) following that particular case.
- If the switch variable does not match any of the case constants, control goes to the statement(s) following the optional default label.
- Hence the use of break statement in the program is to terminate the switch statement when the body of the statement in a particular case has been executed.

Lab Activities

1. Write a program that reads a number and prints its square if it's positive then 10.
2. Write a program that reads two numbers and print the larger.
3. Write the above program using conditional operator.
4. Write a program that reads a number in decimal and a message based on its value as given below

Value (n)	Message to print
90 and above (>=90)	Excellent Performance
80 and above (>=80)	Very Good Performance
70 and above (>=70)	Good Performance

5. Write a program that reads temperature (0 to 5 letters) and prints a message as given below.

Temperature	Message to print
>=30	It is hot
<=15	It is cold
>15	It is cool

6. Write a program that reads temperature (0 to 5 letters) and prints a message as given below.

Name	Gender	Score

7. Write a program that reads basic pay of an employee and calculates and prints his net salary as given below.

Net Pay= Basic Pay + House Rent

Basic Pay	House Rent
10000 and above	2000 if Basic Pay
5000 and above but below 10000	1000 if Basic Pay
Below 5000	500 if Basic Pay